



MATERIAL SAFETY DATA SHEET

Revision Date: 07/14/2003

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: AEROSHELL™ Flight Jacket Oil & Exhaust Remover

MSDS NUMBER: 401260E - 2

PRODUCT CODE(S): 61242

MANUFACTURER

SOPUS Products

P.O. Box 4453

Houston, TX. 77210-4453

TELEPHONE NUMBERS

Spill Information: (877) 242-7400

Health Information: (877) 504-9351

MSDS Assistance Number: (877) 276-7285

SECTION 2

PRODUCT/INGREDIENTS

INGREDIENTS

Carbon-Soot Remover

Inert Ingredients

Isopropyl alcohol

Diethanolamine

Proprietary additives

CAS#

Mixture

67-63-0

111-42-2

Proprietary

CONCENTRATION

80 - 90 %weight

5 - 10 %weight

1 - 3 %weight

1 - 3 %weight

SECTION 3

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Appearance & Odor: Reddish brown liquid. Mild odor.

Health Hazards: Causes severe eye irritation. May be harmful or fatal if swallowed. Do not induce vomiting. May cause aspiration pneumonitis. May cause CNS depression.

Physical Hazards: Material is extremely flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger.

NFPA Rating (Health, Fire, Reactivity): 2, 3, 0

Hazard Rating: Least - 0 Slight - 1 Moderate - 2 High - 3 Extreme - 4

Inhalation:

Breathing of high vapor concentrations may cause CNS depression, evidenced by dizziness, light-headedness, headache, nausea, drowsiness, and loss of coordination. Continued inhalation may result in unconsciousness.

Eye Irritation:

Severely irritating to the eyes causing pain, redness, swelling and blurred vision.

Skin Contact:

May cause slight irritation of the skin. If irritation occurs, a temporary burning sensation and minor redness and/or swelling may result. Other adverse effects not expected from brief skin contact.

Ingestion:

This material may be harmful or fatal if swallowed. Ingestion may result in vomiting; aspiration (breathing) of vomitus into lungs must be avoided as even small quantities may result in aspiration pneumonitis.

Other Health Effects:

Carcinogenic in animal tests.

Refer to Section 11, Toxicological Information, for specific information on the following effects:

Reproductive Toxicity

Primary Target Organs:

The following organs and/or organ systems may be damaged by overexposure to this material and/or its components:

Cardiovascular System, Endocrine System, Eye, Blood/Blood Forming Organs, Reproductive System

Signs and Symptoms:

Irritation as noted above. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin); in severe cases death may occur. Damage to blood-forming organs may be evidenced by: a) easy fatigability and pallor (RBC effect), b) decreased resistance to infection (WBC effect), c) excessive bruising and bleeding (platelet effect).

Aggravated Medical Conditions:

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

For additional health information, refer to section 11.

SECTION 4	FIRST AID MEASURES
------------------	---------------------------

Inhalation:

If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Skin:

Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye:

Flush with water. If irritation occurs, get medical attention. Transport to nearest medical facility for additional treatment.

Ingestion:

DO NOT take internally. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Get medical attention.

SECTION 5	FIRE FIGHTING MEASURES
------------------	-------------------------------

Flash Point [Method]: 107 °F/41.67 °C [Cleveland Open Cup]

Extinguishing Media:

Material will float and can be re-ignited on surface of water. Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water.

Fire Fighting Instructions:

CAUTION! COMBUSTIBLE. Clear fire area of all non-emergency personnel. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus. Container areas exposed to direct flame contact should be cooled with large quantities of water (500 gallons water per minute flame impingement exposure) to prevent weakening of container structure.

Unusual Fire Hazards:

Vapors are heavier than air accumulating in low areas and traveling along the ground away from the handling site. Do not weld, heat or drill on or near container. However, if emergency situations require drilling, only trained emergency personnel should drill.

SECTION 6	ACCIDENTAL RELEASE MEASURES
------------------	------------------------------------

Protective Measures:

CAUTION! COMBUSTIBLE. May burn although not readily ignitable. Eliminate potential sources of ignition. Handling equipment must be bonded and grounded to prevent sparking.

Wear appropriate personal protective equipment when cleaning up spills. Refer to Section 8.

Spill Management:

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

Reporting:

U.S. regulations require reporting releases of this material to the environment which exceed the reportable quantity to the National Response Center at (800)424-8802.

SECTION 7	HANDLING AND STORAGE
------------------	-----------------------------

Precautionary Measures:

Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles such as shoes or belts that cannot be decontaminated. CAUTION! COMBUSTIBLE. Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking. Avoid contact with eyes, skin and clothing.

Handling:

Surfaces that are sufficiently hot may ignite liquid material. Material is extremely flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Storage:

Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

Keep liquid and vapor away from heat, sparks and flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors have dissipated. Use explosion-proof ventilation indoors and in laboratory settings.

Container Warnings:

Keep containers closed when not in use. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical	Limit	TWA	STEL	Ceiling	Notation
Diethanolamine	ACGIH TLV	2 mg/m3			
Isopropyl Alcohol	ACGIH TLV	400 ppmv	500 ppmv		
Isopropyl Alcohol	OSHA PEL	400 ppmv	500 ppmv		
Isopropyl Alcohol	OSHA PEL - 1989(revoked)	400 ppmv			

Exposure Controls

Adequate explosion-proof ventilation indoors and in laboratory settings to control airborne concentrations below the exposure guidelines/limits. Eye washes and showers for emergency use.

Personal Protection

Personal protective equipment (PPE) selections vary based on potential exposure conditions such as handling practices, concentration and ventilation. Information on the selection of eye, skin and respiratory protection for use with this material is provided below.

Eye Protection:

Chemical Goggles, or Safety glasses with side shields

Skin Protection:

Use protective clothing which is chemically resistant to this material. Selection of protective clothing depends on potential exposure conditions and may include gloves, boots, suits and other items. The selection(s) should take into account such factors as job task, type of exposure and durability requirements.

Published literature, test data and/or glove and clothing manufacturers indicate the best protection is provided by:

Butyl, or Nitrile Rubber

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Types of respirator(s) to be considered in the selection process include:

For Vapors: Air Purifying, R or P style prefilter & organic cartridge, NIOSH approved respirator.

Self-contained breathing apparatus for use in environments with unknown concentrations or emergency

situations.

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES
------------------	---

Appearance & Odor: Reddish brown liquid. Mild odor.

Boiling Point	> 140 °F	Evaporation Rate	1.6
Flash Point	107 °F [Cleveland Open Cup]	Solubility (in Water)	Completely Soluble
Specific Gravity	0.991	Vapor Density	2.2
Viscosity	< 10 cSt @ 40 °C	Volatility	99.9 %volume

SECTION 10	REACTIVITY AND STABILITY
-------------------	---------------------------------

Stability:

Material is stable under normal conditions.

Conditions to Avoid:

Avoid heat and open flames.

Materials to Avoid:

Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products:

Thermal decomposition products are highly dependent on combustion conditions. A complex mixture of airborne solids, liquids and gases will evolve when this material undergoes pyrolysis or combustion. Carbon Monoxide, Carbon Oxides, Nitrogen Oxides and other unidentified organic compounds may be formed upon combustion.

SECTION 11	TOXICOLOGICAL INFORMATION
-------------------	----------------------------------

Acute Toxicity

TEST	Result	OSHA Classification	Material Tested
Dermal LD50	> 2.0 g/kg(Rabbit)	Non-Toxic	Based on components(s)
Oral LD50	> 2.0-5.0 g/kg(Rat)	Non-Toxic	Based on components(s)

Carcinogenicity Classification

Chemical Name	NTP	IARC	ACGIH	OSHA
Carbon-Soot Remover	No	No	No	No

Toxic Effects - Exhaust Remover

Carcinogenicity	Contains diethanolamine. Clear evidence of carcinogenic activity of diethanolamine in male and female B6C3F1 mice was observed based on increased incidences of liver neoplasms in males and females and increased incidences of renal tubule neoplasms in males. No evidence of carcinogenicity was seen in similarly exposed rats.
Cardiovascular	Repeated oral and dermal exposure to diethanolamine has been shown to produce microscopic evidence of

System	damage to cardiac (heart) cells in mice.
Endocrine System	Two-year exposure of mice to diethanolamine produced microscopic changes in the thyroid gland (follicular cell hyperplasia).
Eye	Ingestion of this product can lead to blindness.
Blood/Blood Forming Organs	Rats exposed dermally or orally to diethanolamine may develop anemia (a decreased number of circulating red blood cells).
Neurotoxicity	Components of this product are rapidly absorbed when inhaled. Inhalation exposures can lead to severe intoxication, dizziness, visual impairment, nausea, headaches, narcosis, muscular incoordination and respiratory failure. Oral and dermal diethanolamine exposure to male and female rats resulted in microscopic changes in the central nervous system. Demyelination (loss of nerve insulation) was observed in portions of the brain and spinal cord.
Reproductive System	Rats consuming drinking water containing diethanolamine for 2 or 13 weeks showed evidence of degeneration of the seminiferous tubules of the testis. Sperm count and motility were also decreased in the 13 week study.
Systemic Toxicity	Systemic effects are possible following extensive skin contact. Dermal and/or oral exposure to diethanolamine has produced a variety of liver and kidney effects in rats and mice. The most common reported liver effect has been increased liver weight, which at high doses is sometimes associated with necrosis (liver cell death). Decreases in kidney function in rats, nephropathy and various microscopic changes have also been reported.

SECTION 12	ECOLOGICAL INFORMATION
-------------------	-------------------------------

Environmental Impact Summary:

There is no ecological data available for this product. However, this product is an oil. It is persistent and does not readily biodegrade. However, it does not bioaccumulate.

SECTION 13	DISPOSAL CONSIDERATIONS
-------------------	--------------------------------

RCRA Information:

If this material, as it is originally purchased, were subsequently DISCARDED as a waste, the waste would be a RCRA hazardous waste. D001 (Ignitable Hazardous Waste)

Under RCRA, it is the responsibility of the user of the material to determine, at the time of the disposal, whether the material meets RCRA criteria for hazardous waste. This is because material uses, transformations, mixtures, processes, etc. may affect the classification. Refer to the latest EPA, state and local regulations regarding proper disposal.

SECTION 14	TRANSPORT INFORMATION
-------------------	------------------------------

US Department of Transportation Classification

PRODUCT CODE(S): 61242

AEROSHELL™ Flight Jacket Oil & Exhaust Remover

WARNING!

CAUSES SEVERE EYE IRRITATION. OVEREXPOSURE TO VAPORS CAN CAUSE CNS DEPRESSION. MAYBE HARMFUL OR FATAL IF SWALLOWED. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE.

MAY CAUSE DAMAGE TO: Cardiovascular System, Endocrine System, Eye, Blood/Blood Forming Organs, Reproductive System

Refer to Section 11, Toxicological Information, for specific information on the following effects:
Reproductive Toxicity

<p>Precautionary Measures: Avoid prolonged or repeated contact with eyes, skin and clothing. Avoid heat and open flames. Avoid breathing of vapors, fumes, or mist. Do not take internally. Use only with adequate ventilation. Keep container closed when not in use. Wash thoroughly after handling.</p>

FIRST AID

Inhalation: DO NOT attempt to rescue victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Skin Contact: Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

Eye Contact: Flush with water. If irritation occurs, get medical attention.

Ingestion: DO NOT take internally. DO NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Get medical attention.

FIRE

In case of fire, Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water. Material will float and can be re-ignited on surface of water.

SPILL OR LEAK

Dike and contain spill.

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

CONTAINS: Inert Ingredients, Mixture; Isopropyl alcohol, 67-63-0; Diethanolamine, 111-42-2; Proprietary additives,

Proprietary

NFPA Rating (Health, Fire, Reactivity): 2, 3, 0

TRANSPORTATION

US Department of Transportation Classification

Proper Shipping Name: Consumer commodity
Technical Names (s): Contains Isopropyl Alcohol
Hazard Class/Division: ORM-D
Packing Group: III

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flames or heat. Keep container closed and drum bungs in place.

Name and Address
SOPUS Products
P.O. Box 4453
Houston, TX 77210-4453

ADMINISTRATIVE INFORMATION

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4453, Houston, TX. 77210-4453
Company Product Stewardship & Regulatory Compliance Contact: Timothy W Childs
Phone Number: (281) 874-7708

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT : IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT DATA, IS THE PROPERTY OF SOPUS PRODUCTS AND IS NOT TO BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF SOPUS PRODUCTS.

38556-12021-100R-07/14/2003

