



# Shell V Power Petrol

## 95 Octane (RON)



### DESCRIPTION

Shell V Power petrol is manufactured to meet the NZ Petroleum Products Specifications Regulations 2002.

Shell V Power is a quality premium petrol that has been especially designed to improve the engine responsiveness. V Power petrol contains Shell's advanced additive technology, which is designed to protect the engine from the build up of harmful deposits. This improves performance by keeping clean fuel injectors, carburettors and inlet valves and leads to consistently good gasoline/air mixture preparation, better combustion and better driveability.

### HEALTH & SAFETY

Shell V Power petrol is classified according to Hazardous Substances (Classifications) Regulation 2001 as 3.1A - Flammable liquid, Very High Hazard. Avoid contact with the skin and eyes, and breathing vapours or mists.

For further guidance on product health and safety refer to the appropriate Shell Material Safety Data Sheet.

### TYPICAL CHARACTERISTICS

DESCRIPTION	UNITS	METHODS	TYPICAL
			V Power
Colour	-	Visual	Yellow
Octane Number	-	ASTM D2699	95.2
Distillation	-	ASTM D86	
% evaporated @ 70°C	%	-	25
% evaporated @ 100°C	%	-	47
% evaporated @ 150°C	%	-	87
Final Boiling Point	°C.	-	200
Copper Corrosion (2 hr @ 100 °C)	-	ASTM D130	1a
Benzene	% vol.	ASTM D5580	0.95
Sulphur	mg/kg	ASTM D5453	20

#### Document Information

Date Revised: 01/05/2008