



SHELL RACING FUEL – MOTORCYCLE GP 4T

Application

Shell Racing Fuel – Motorcycle GP 4T is a special unleaded fuel designed for maximum power delivery in four-stroke road racing motorcycles. It meets the relevant FIM regulations.

Comments for Use

The fuel should be stored in closed and preferably full fuel containers under dry and cool conditions to maintain maximum performance potential.

Characteristics

This fuel is designed to provide ideal performance and smooth power generation in high-revving bikes, reaching speeds of 310kph with rapid acceleration as required in MotoGP engines in the World Championship. The fuel also offers high flame speeds.

Properties

Typical Values

Article 252 (excerpt)

Density 765	740 – 750 kg/m ³	720 – 780 kg/m ³
RON 101	100 – 101	95 – 102
MON 89	88 – 89	85 – 90
RVP 40	60 – 70 kPa	max 90 kPa
Oxygen Content	2.5 – 2.6 Mass%	max 2.7 Mass%
Lead Content	<1 mg/L	max 5 mg/L
Benzene Content	<1 Vol%	max 1 Vol%



Due to continuous improvement of the product and production process, small changes in the actual values may occur. July 2006

Please contact Shell Racing Solutions for further information

Europe

Tel: +44 151 373 5950

Asia-Pacific

Tel: +60 3 2170 3888

North America

Tel: +1 866 312 8498

Email us at shellracing@shell.com

Or visit our website at www.shell.com/globalsolutions/racing

Shell Racing Solutions is a division of Shell Global Solutions. Shell Global Solutions is a network of independent technology companies in the Royal Dutch/Shell Group. In this document, the expression 'Shell Global Solutions' is sometimes used for convenience where reference is made to these companies in general, or where no useful purpose is served by identifying a particular company.

This document is intended for general information purposes only and does not in any way constitute an offer to provide specific services. Some services may not be available in certain countries or political subdivisions thereof.

GS022053407-En(B)