



# ShellSol D100

<b>Product Code</b>	Q7732
<b>Region</b>	Europe
<b>Product Category</b>	Aliphatic Mineral Spirits
<b>CAS Registry Number</b>	64742-47-8
<b>EINECS Number</b>	265-149-8
<b>Description</b>	ShellSol D100 consists predominantly of C13- C15 paraffins and naphthenes. Deep hydrogenation gives this solvent a very low aromatic content, negligible amount of reactive impurities and a low, sweet odour.

## Typical Properties

Property	Unit	Method	Value
Water	% m/m	ASTM D1364	< 0.005
Density @15°C	kg/L	ASTM D4052	0.803
Coefficient of Cubic Expansion @20°C	10 <sup>-4</sup> /°C	Calculated	9
Refractive Index @20°C	-	ASTM D1218	1.443
Colour	Saybolt	ASTM D156	+30
Bromine Index	mg Br/100g	ASTM D1492	< 10
Copper Corrosion (1hr @100°C)	-	ASTM D130	1
Doctor Test	-	ASTM D4952	Negative
Non Volatile Matter	mg/100ml	ASTM D1353	1
Distillation, Initial Boiling Point	°C	ASTM D86	234
Distillation, Dry Point	°C	ASTM D86	259
Relative Evaporation Rate (nBuAc=1)	-	ASTM D3539	< 0.01
Relative Evaporation Rate (Ether=1)	-	DIN 53170	> 3900
Antoine Constant A #	kPa, °C	-	7.41890
Antoine Constant B #	kPa, °C	-	2603.5
Antoine Constant C #	kPa, °C	-	241.460

Antoine Constants: Temperature range	°C	-	0 to +100
Vapor Pressure @ 0°C	kPa	Calculated	< 0.01
Vapor Pressure @ 20°C	kPa	Calculated	< 0.01
Saturated Vapor Concentration @ 20°C	g/m <sup>3</sup>	Calculated	0.2
Paraffins	% m/m	GC	55
Naphthenes	% m/m	GC	45
Aromatics	mg/kg	SMS 2728	200
Benzene	mg/kg	GC	< 3
Sulfur	mg/kg	ISO 20846	< 0.5
Flash Point	°C	ASTM D93	103
Lower Explosion Limit in Air	% v/v		0.5
Upper Explosion Limit in Air	% v/v		5.5
Auto Ignition Temperature	°C	ASTM E659	232
Electrical Conductivity @ 20°C	pS/m	ASTM D4308	< 1
Dielectric Constant @ 20°C	-	-	2.1
Aniline Point	°C	ASTM D611	83
Kauri-Butanol Value	-	ASTM D1133	26
Pour Point	°C	ASTM D97	-26
Viscosity @ 25°C	mm <sup>2</sup> /s	ASTM D445	2.9
Surface Tension @ 20°C	mN/m	Du Nouy ring	28
Thermal Conductivity @ 20°C	W/m/°C		0.14
Hildebrand Solubility Parameter	(cal/cm <sup>3</sup> ) <sup>1/2</sup>	-	7.5
Hydrogen Bonding Index	-	-	0
Fractional Polarity	-	-	0
Heat of Vaporization at T <sub>boil</sub>	kJ/kg	-	250
Heat of Combustion (Net) @t 25°C	kJ/kg	-	45000
Specific Heat @ 20°C	kJ/kg/°C	-	2.1
Molecular Weight	g/mol	Calculated	206

(#) In the Antoine temperature range, the vapor pressure P (kPa) at temperature T (°C) can be calculated by means of the Antoine equation:  $\log P = A - B/(T+C)$

## Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM) : [www.astm.org](http://www.astm.org)  
International Organization for Standardization (ISO) : [www.iso.org](http://www.iso.org)  
Deutsches Institut für Normung (DIN) : [www.din.de](http://www.din.de)

Shell Method Series (SMS) methods are issued by Shell Global Solutions International B.V., Shell Technology Centre, Amsterdam, The Netherlands. Requests for copies of SMS can be made through your local Shell Chemicals company.

N.B: For routine quality control local test methods may be applied. Such methods have been validated against those mentioned in this datasheet.

## Quality

ShellSol D100 as produced, meets the volatile organic compound (VOC) exemption criteria and definition of LVP-VOC as established in CARB's Consumer Products Regulation; in the USEPA's National Volatile Organic Compound Emissions Standards for Consumer Products; and in the Model Rule for Consumer Products as adopted by the Ozone Transport Commission (OTC) . Due to their low volatility and photochemical reactivity, these LVP-VOCs are fully exempt and non-reportable VOCs in calculations of the VOC contents of regulated consumer product categories.

ShellSol D100 does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

## Hazard Information

For detailed Hazard Information please refer to the Safety Data Sheet on [www.shell.com/chemicals](http://www.shell.com/chemicals).

## Storage Handling

Provided proper storage and handling precautions are taken we would expect ShellSol D100 to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Safety Data Sheet on [www.shell.com/chemicals](http://www.shell.com/chemicals).

## Trademark

ShellSol is a Shell trademark.

All products purchased or supplied by Shell chemicals companies are subject to the terms and conditions set out in the contract, order confirmation and/or bill of lading. All other information supplied by Shell chemicals companies, including that herein, is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine a product's suitability for a particular purpose. Except as may be set forth in the applicable contract, order confirmation and/or bill of lading, Shell chemicals companies make no warranty, express or implied, including regarding any information supplied or the data upon which it is based or the results to be obtained from the use of such products or information, or concerning product, whether of satisfactory quality, merchantability, fitness for any particular purpose or otherwise, or with respect to intellectual property infringement as a result of use of information or products, and none shall be implied.

The expression 'Shell Chemicals' refers to the companies of the Royal Dutch/Shell Group that are engaged in chemical businesses. Each of the companies that make up the Royal Dutch/Shell Group of companies is an independent entity and has its own separate identity.