



Data Sheet

IS 2.1.116

Issued November 2001, 1st Edition

Product name

SHELLSOL TK

Description

SHELLSOL TK is a narrow boiling range, medium evaporating solvent widely used in the aerosol and speciality formulating industry.

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
Distillation range,	ASTM D1078	°C	
IBP			181
DP			202
Flash point	IP 170	°C	57
Aniline Point	ASTM D611	°C	80
Density @ 15 °C	ASTM D4052/D1298	Kg/l	0.769
Conductivity @23 °C	ASTM D2624	pS/m	10
Composition		% m	
Paraffins			>99.8
Napthenes			<0.1
Aromatics			<0.1

Test methods

ASTM methods are published by the American Society for Testing and Materials 1916 Race St, Philadelphia, Pa. U.S.A.

IP methods are published by the Institute of Petroleum, 61 New Cavendish St, 6 London, U.K.

General information

SHELLSOL TK is flammable (Flash Point 57 °C), can form explosive mixtures with air and is immiscible with water. It should be kept away from heat, naked flames and sparks. Electrostatic charge may be generated during handling, e.g. pumping. In case of fire, carbon dioxide, dry chemical powder, foam, sand or earth should be used, but not water jets.

Occupational exposure to solvents should be reduced to the lowest practicable level. Continuous inhalation of the vapour should be avoided. Prolonged and repeated skin contact can cause dermatitis due to defatting properties. In the event of contact with the product, the following first aid precautions should be observed:

Skin

Flush the eyes with water. If irritation persists obtain medical attention.

Ingestion

Do not induce vomiting. Obtain medical attention.

Inhalation

Remove to fresh air. If rapid recovery does not occur, obtain medical attention.

The information contained in this bulletin is, to the best of our knowledge, true and accurate, but any recommendations or suggestions, which may be made, are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.