



# Hexane Extraction

<b>Product Code</b>	Q1252
<b>Region</b>	Europe
<b>Product Category</b>	Special Boiling Point Solvents
<b>CAS Registry Number</b>	64742-49-0
<b>EINECS Number</b>	265-151-9
<b>Description</b>	Hexane Extraction Grade is manufactured to the high standards required by the food and extraction industry. The solvent contains about 50% n-hexane, with a similar content of other hexane isomers. It is very low in aromatics, olefins and other impurities.

## Typical Properties

Property	Unit	Method	Value
Water	% m/m	ASTM D1364	< 0.005
Density @15°C	kg/L	ASTM D4052	0.676
Coefficient of Cubic Expansion @20°C	10 <sup>-4</sup> /°C	Calculated	13
Refractive Index @20°C	-	ASTM D1218	1.380
Colour	Saybolt	ASTM D156	+30
Bromine Index	mg Br/100g	ASTM D1492	< 5
Copper Corrosion (1hr @100°C)	-	ASTM D130	1
Doctor Test	-	ASTM D4952	Negative
Non Volatile Matter	mg/100ml	ASTM D1353	< 0.5
Distillation, Initial Boiling Point	°C	ASTM D1078	66
Distillation, Dry Point	°C	ASTM D1078	70
Relative Evaporation Rate (nBuAc=1)	-	ASTM D3539	8.0
Relative Evaporation Rate (Ether=1)	-	DIN 53170	1.4
Antoine Constant A #	kPa, °C	-	7.38070
Antoine Constant B #	kPa, °C	-	2110.27
Antoine Constant C #	kPa, °C	-	326.200
Antoine Constants: Temperature range	°C	-	+20 to +70

Vapor Pressure @ 0°C	kPa	Calculated	8.2
Vapor Pressure @ 20°C	kPa	Calculated	19
Saturated Vapor Concentration @ 20°C	g/m <sup>3</sup>	Calculated	681
Paraffins	% m/m	GC	85
Naphthenes	% m/m	GC	15
Aromatics	mg/kg	SMS 2728	< 5
Benzene	mg/kg	GC	< 3
n-Hexane	%m/m	GC	50
Sulfur	mg/kg	ISO 20846	< 0.5
Flash Point, (Abel)	°C	IP170	< -30
Lower Explosion Limit in Air	% v/v		1.1
Upper Explosion Limit in Air	% v/v		7.4
Auto Ignition Temperature	°C	ASTM E659	375
Electrical Conductivity @ 20°C	pS/m	ASTM D4308	< 1
Aniline Point	°C	ASTM D611	65
Kauri-Butanol Value	-	ASTM D1133	31
Pour Point	°C	ASTM D97	< -50
Viscosity @ 25°C	mm <sup>2</sup> /s	ASTM D445	0.49
Surface Tension @20°C	mN/m	Du Nouy ring	19
Thermal Conductivity @ 20°C	W/m/°C		0.12
Hildebrand Solubility Parameter	(cal/cm <sup>3</sup> ) <sup>1/2</sup>	-	7.3
Hydrogen Bonding Index	-	-	0
Fractional Polarity	-	-	0
Heat of Vaporization at T <sub>boil</sub>	kJ/kg	-	333
Heat of Combustion (Net) @t 25°C	kJ/kg	-	46000
Specific Heat @ 20°C	kJ/kg/°C	-	2.2
Molecular Weight	g/mol	Calculated	86

(#) In the Antoine temperature range, the vapor pressure P (kPa) at temperature T (°C) can be calculated by means of the Antoine equation:  $\log P = A - B/(T+C)$

## Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM) : [www.astm.org](http://www.astm.org)  
International Organization for Standardization (ISO) : [www.iso.org](http://www.iso.org)  
Deutsches Institut für Normung (DIN) : [www.din.de](http://www.din.de)

Shell Method Series (SMS) methods are issued by Shell Global Solutions International B.V., Shell Technology Centre, Amsterdam, The Netherlands. Requests for copies of SMS can be made through your local Shell Chemicals company.

N.B: For routine quality control local test methods may be applied. Such methods have been validated against those mentioned in this datasheet.

## Quality

Hexane Extraction Grade can be supplied to meet the requirements of ASTM D1836. Its composition complies with the FAO/WHO and UK MAFF specifications for polycyclic aromatics and heavy metals. Hexane Extraction grade does not contain detectable quantities of chlorinated compounds.

## Hazard Information

For detailed Hazard Information please refer to the Safety Data Sheet on [www.shell.com/chemicals](http://www.shell.com/chemicals).

## Storage Handling

Provided proper storage and handling precautions are taken we would expect Hexane Polymerisation Grade to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Safety Data Sheet on [www.shell.com/chemicals](http://www.shell.com/chemicals).

All products purchased or supplied by Shell chemicals companies are subject to the terms and conditions set out in the contract, order confirmation and/or bill of lading. All other information supplied by Shell chemicals companies, including that herein, is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine a product's suitability for a particular purpose. Except as may be set forth in the applicable contract, order confirmation and/or bill of lading, Shell chemicals companies make no warranty, express or implied, including regarding any information supplied or the data upon which it is based or the results to be obtained from the use of such products or information, or concerning product, whether of satisfactory quality, merchantability, fitness for any particular purpose or otherwise, or with respect to intellectual property infringement as a result of use of information or products, and none shall be implied.

The expression 'Shell Chemicals' refers to the companies of the Royal Dutch/Shell Group that are engaged in chemical businesses. Each of the companies that make up the Royal Dutch/Shell Group of companies is an independent entity and has its own separate identity.

