



Data Sheet

Issued:

22-Nov-2007

Product Name

SBP 80/95 LNH

Product Code
Q5115 Europe
Product Category
Special Boiling Point Solvents
CAS Registry Number

64742-49-0

EINECS Number

265-151-9

Description

SBP80/95 LNH is a C6-C7 hydrocarbon solvent with a n-hexane content of less than 3%. Being made from hydrogenated feedstock, its aromatics and olefins content is very low.

Typical Properties

Property	Unit	Method	Value
Density @15°C	kg/l	ASTM D4052	0.719
Cubic Expansion Coefficient @20°C	(10 ⁻⁴)/°C	Calculated	13
Refractive Index @20°C	-	ASTM D1218	1.399
Color	Saybolt	ASTM D156	+30
Bromine Index	mg Br/100g	ASTM D1492	< 5
Copper Corrosion (3hr @100°C)	-	ASTM D130	1
Doctor Test	-	ASTM D235	Negative
Non Volatile Matter	mg/100ml	ASTM D1353	1
Distillation, IBP	°C	ASTM D1078	86
Distillation, DP	°C	ASTM D1078	93
Relative Evaporation Rate (nBuAc=1)	-	ASTM D3539	4.8
Relative Evaporation Rate (Ether=1)	-	DIN 53170	2.9
Antoine Constant A #	kPa, °C	-	7.64250
Antoine Constant B #	kPa, °C	-	2450.95
Antoine Constant C #	kPa, °C	-	348.070
Antoine Constants: Temperature range	°C	-	+25 to +85
Vapor Pressure @0°C	kPa	Calculated	4.0
Vapor Pressure @20°C	kPa	Calculated	9.6
Saturated Vapor Concentration @20°C	g/m ³	Calculated	376
n-Paraffins	% m/m	GC	11
Isoparaffins	% m/m	GC	49
Paraffins	% m/m	GC	60
Naphthenes	% m/m	GC	40

Aromatics	mg/kg	SMS 2728	< 5
Benzene	mg/kg	GC	< 3
n-Hexane	% m/m	GC	2
Sulfur	mg/kg	SMS 1897	< 0.5
Flash Point	°C	IP 170	-15
Auto Ignition Temperature	°C	ASTM E659	417
Explosion Limit: Lower	%v/v	-	1.0
Explosion Limit: Upper	%v/v	-	7.2
Electrical Conductivity @20°C	pS/m	ASTM D4308	< 1
Aniline Point	°C	ASTM D611	57
Kauri-Butanol Value	-	ASTM D1133	35
Pour Point	°C	ASTM D97	< -50
Surface Tension @20°C	mN/m	Du Nouy ring	21
Viscosity @25°C	mm ² /s	ASTM D445	0.63
Hildebrand Solubility Parameter	(cal/cm ³) ^{1/2}	-	7.4
Hydrogen Bonding Index	-	-	0
Fractional Polarity	-	-	0
Heat of Vaporization @Tboil	kJ/kg	-	321
Heat of Combustion (Net) @25°C	kJ/kg	-	45500
Specific Heat @20°C	kJ/kg/°C	-	2.1
Thermal Conductivity @20°C	W/m/°C	-	0.12
Molecular Weight	g/mol	Calculated	95

(#) In the Antoine temperature range, the vapor pressure P (kPa) at temperature T (°C) can be calculated by means of the Antoine equation: $\log P = A - B/(T+C)$

Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM) : www.astm.org
Energy Institute (IP) : www.energyinst.org.uk
Deutsches Institut für Normung (DIN) : www.din.de

Shell Method Series (SMS) methods are issued by Shell Global Solutions International B.V., Shell Research and Technology Centre, Amsterdam, The Netherlands. Copies of SMS can be obtained through your local Shell Chemicals company.

For routine quality control analyses, local test methods may be applied that are different from those mentioned in this datasheet. Such methods have been validated and can be obtained through your local Shell Chemicals company.

Quality

SBP 80/95 LNH does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

Hazard Information

For detailed Hazard Information please refer to the Material Safety Data Sheet on www.shell.com/chemicals.

Storage and Handling

Provided proper storage and handling precautions are taken we would expect SBP 80/95 LNH to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Material Safety Data Sheet on www.shell.com/chemicals.

Warranty

All products purchased or supplied by Shell Chemicals are subject to terms and conditions set out in the contract, order acknowledgment and/or bill of lading. Shell Chemicals warrant that their product will meet those specifications designated as such herein or in other publications. All other information including that herein, supplied by Shell Chemicals is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine the products' suitability for a particular purpose. Shell Chemicals make no other warranty either expressed or implied, regarding such other information, the data upon which the same is based, or the results to be obtained from use thereof; that any products shall be merchantable or fit for any purpose; or that the use of such other information or product will not infringe any patent.

The expression 'Shell Chemicals' refers to the companies of the Shell Group that are engaged in chemical businesses. Each of the companies that make up the Shell Group of companies is an independent entity and has its own separate identity.