



Data Sheet

Issued:

23-Jul-2009

Product Name

SBP 140/165

Product Code
Q5911 Africa
Product Category
Special Boiling Point Solvents
CAS Registry Number

64742-49-0

EINECS Number

265-151-9

Description

SBP 140/165 is a C8-C10 hydrocarbon solvent. It may also be considered as a low flash hydrotreated white spirit (ShellSol D25). Being made from hydrogenated feedstock, its aromatics and olefins content is very low.

Typical Properties

Property	Unit	Method	Value
Density @15°C	kg/l	ASTM D4052	0.750
Cubic Expansion Coefficient @20°C	(10 ⁻⁴)/°C	Calculated	12
Refractive Index @20°C	-	ASTM D1218	1.417
Color	Saybolt	ASTM D156	+30
Bromine Index	mg Br/100g	ASTM D1492	< 5
Doctor Test	-	ASTM D235	Negative
Distillation, IBP	°C	ASTM D1078	143
Distillation, DP	°C	ASTM D1078	161
Relative Evaporation Rate (nBuAc=1)	-	ASTM D3539	0.56
Antoine Constant A #	kPa, °C	-	7.60100
Antoine Constant B #	kPa, °C	-	2768.44
Antoine Constant C #	kPa, °C	-	350.000
Antoine Constants: Temperature range	°C	-	+20 to +145
Vapor Pressure @0°C	kPa	Calculated	0.49
Vapor Pressure @20°C	kPa	Calculated	1.3
Saturated Vapor Concentration @20°C	g/m ³	Calculated	69
Paraffins	% m/m	GC	65
Naphthenes	% m/m	GC	35
Aromatics	mg/kg	SMS 2728	< 5
Benzene	mg/kg	GC	< 3
Sulfur	mg/kg	SMS 1897	< 0.5
Flash Point	°C	IP 170	26
Auto Ignition Temperature	°C	ASTM E659	287

Explosion Limit: Lower	%v/v	-	0.8
Explosion Limit: Upper	%v/v	-	6.0
Electrical Conductivity @20°C	pS/m	-	< 1
Aniline Point	°C	ASTM D611	67
Kauri-Butanol Value	-	ASTM D1133	32
Pour Point	°C	ASTM D97	< -50
Surface Tension @20°C	mN/m	Du Nouy ring	22
Viscosity @25°C	mm ² /s	ASTM D445	0.94
Hildebrand Solubility Parameter	(cal/cm ³) ^{1/2}	-	7.5
Hydrogen Bonding Index	-	-	0
Fractional Polarity	-	-	0
Molecular Weight	g/mol	Calculated	128

(#) In the Antoine temperature range, the vapor pressure P (kPa) at temperature T (°C) can be calculated by means of the Antoine equation: $\log P = A - B/(T+C)$

Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM) : www.astm.org

Energy Institute (IP) : www.energyinst.org.uk

Shell Method Series (SMS) methods are issued by Shell Global Solutions International B.V., Shell Research and Technology Centre, Amsterdam, The Netherlands. Copies of SMS can be obtained through your local Shell Chemicals company.

For routine quality control analyses, local test methods may be applied that are different from those mentioned in this datasheet. Such methods have been validated and can be obtained through your local Shell Chemicals company.

Quality

SBP 140/165 does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

Applications

SBP 140/165 is used in the paper, rubber and chemical process industries, and in household products, surface coatings, printing inks, adhesives, pesticide formulations, waxes and polishes. It is also used as an extraction solvent and in degreasing.

Hazard Information

For detailed Hazard Information please refer to the Material Safety Data Sheet on www.shell.com/chemicals.

Storage and Handling

Provided proper storage and handling precautions are taken we would expect SBP 140/165 to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Material Safety Data Sheet on www.shell.com/chemicals.

Warranty

All products purchased or supplied by Shell Chemicals are subject to terms and conditions set out in the contract, order acknowledgment and/or bill of lading. Shell Chemicals warrant that their product will meet those specifications designated as such herein or in other publications. All other information including that herein, supplied by Shell Chemicals is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine the products' suitability for a particular purpose. Shell Chemicals make no other warranty either expressed or implied, regarding such other information, the data upon which the

same is based, or the results to be obtained from use thereof; that any products shall be merchantable or fit for any purpose; or that the use of such other information or product will not infringe any patent.

The expression 'Shell Chemicals' refers to the companies of the Shell Group that are engaged in chemical businesses. Each of the companies that make up the Shell Group of companies is an independent entity and has its own separate identity.

Trademark

ShellSol is a Shell Trademark.