

# Cargo Handling Sheet

Non Shell Product Supplied by Third  
Party

NEXBASE 3060

Document Date: 02 June 2017  
Revision 0

*This Cargo Handling Sheet is for the use of vessels  
chartered by Shell Chemicals or SETL or SIETCO*

Product supplied by Third Party; Information is obtained from supplier's SDS and other reference publications. CHS is for reference only.

### Product Details

Product Name:	NEXBASE 3060
Shipping Name:	Noxious liquid, NF, (5) n.o.s. (NEXBASE 3060, contains Cycloalkanes C 12+), ST 2, Cat. Y
Chemical Family:	Lubricating oils (petroleum)
Product Code:	Not a Shell product
SDS:	Supplier to provide (Neste Oil)

### Physical Properties

Relative density:	0.83-0.85 (15°C / 59 °F)
Kinematic Viscosity:	typical value, 32 mm <sup>2</sup> /s (40°C / 104 °F)
D. Viscosity = 50 mPas @:	27 °C / 80.6 °F
Vapor Pressure:	< 0.1 hPa (20 °C / 68 °F)
Boiling Point:	370-600 °C / 698-1112 °F
Melting Point:	≤ -12 °C / 10.4 °F
Flash Point:	> 220°C / 428 °F
Appearance:	Colourless, Clear

**Note 1:** Physical Properties are for reference only and valid as of date of this revision; see loading terminal for specific properties.

**Transshipment** Prior to arranging transshipment, Charterers must agree to Owner's proposed plan

### Marpol Details

Marpol Annex:	II
IMO Ship Type:	2
Inland Barge:	Double Hull
IMO Pollution Category:	Y

IBC 16.2.6:	Yes
IBC 16.2.9:	No, see IBC Chapter 17 footnote (I)
Pre-Wash Required:	No pre-wash required when discharged in accordance with CHS
Compatibility Group:	USCG compatibility group 33

### Cargo Handling Requirements

N2 Purge Cargo Tanks Prior Loading:	No
N2 Blanket Required:	Yes for voyages > 10 days' duration; PQ Requirement; 8% O <sub>2</sub>
Adjacent Space Purge:	No
Loading Temperature Range:	Ambient to 50°C / 122°F
Transit Temperature Range:	Ambient to loading temperature
Discharge Temperature Range:	> 27°C / 81°F
Maximum Heating Coil Temperature:	50°C / 122°F during transit; 90°C / 194°F during discharge
Adjacent Maximum Cargo Temperature:	50°C / 122°F

**Note 1:** Carrier to verify with supplier carriage requirements; if different from these, please notify responsible Shell charterer.

**Note 2:** If Nitrogen blanket is in place and Carrier chooses to tranship, carrier must reapply nitrogen blanket on the cargo, both on the discharging and receiving ship, at their time, risk, and expense.

**Note 3:** PQ = Product Quality

**Note 4:** N2 Blanket Guidance:

- a. O<sub>2</sub> level in tanks: 8%
- b. Vessel to maintain a constant nitrogen overpressure of 20 millibars or more during the voyage
- c. Surveyor to record in survey report the type of cargo monitoring system and nitrogen replenishment system used onboard the vessel
- d. Vessel to keep a daily N<sub>2</sub> log of each tank:
  1. Tank pressure
  2. O<sub>2</sub> level
  3. Tank Temperature

Log is to be presented to receiver at time of discharge and a copy sent to Charterers.

### Regional Requirements

**Note 1:** None known; Check with supplier for any additional regional requirements

## Tank Acceptance Requirements

All nominated shipboard cargo handling systems are to be presented clean (residual free), dry, odor free, rust free, with good gaskets, fit to load this cargo.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N<sub>2</sub>, and blanked off.

<b>Stainless Steel or Coated Tank:</b>	Either, carrier to verify suitability of coating for product
<b>Prior Cargo Restrictions:</b>	No
<b>Wall Wash Required:</b>	No

## Safety Information and Incident Reporting

### Safety Information:

For more detailed information, refer to the SDS or e-SDS for reportable spill/release quantities whether in the water, air or ground.

### Incident Reporting:

**International Registered Vessels:** If an incident occurs call Shell International Trading and Shipping in London on +442079347777.

**Jones Act Vessels:** call the Shell 24 hr. incident number at +17132412532. The USA National Response Center telephone number is +18004248802.

For additional marine cargo handling advice or information, contact Captain Ajit Warty at +6563907259.

### Disclaimer

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.