

Cargo Handling Sheet

Non-Shell Chemical Product

GPII 100N

Document Date: 22 May 2020

Revision 1

Cargo Handling Sheets are for the use of vessels chartered to Shell Chemicals

Information is obtained from supplier's SDS and other reference publications.

Product Details

Product Name:	GPII 100N
Shipping Name:	Distillates (petroleum), hydrotreated heavy paraffinic
Chemical Family:	Base Oils
Product Code:	002D5497
SDS:	Shell Trading (US) Company

Physical Properties

Density:	820 - 840 kg/m ³ (15 °C / 59 °F)
Kinematic Viscosity:	>= 2 mm ² /s (40.0 °C / 104.0 °F)
Vapor Pressure:	0.01 kPa (38.0 °C / 100.4 °F)
Boiling Point:	208 - 800 °C / 406 - 1472 °F
Pour Point:	Data not available
Flash Point:	199 - 344 °C / 390 - 651 °F
Appearance:	Undyed liquid, Unstened Odour

Note 1: Physical Properties are for reference only and valid as of date of this revision; see loading terminal for parcel specific physical properties.

Note 2: Hazard Identification: Potential Static Accumulator

Transhipments

Prior to arranging transhipment Charterer must agree to Owner's proposed plan. When arranged by the Owner, Owner must ensure that all transhipment vessels comply with the requirements of this cargo handling sheet.

Marpol Details

Marpol Annex:	1
IMO Ship Type:	Double hulled vessels certified for the carriage of oil
Inland Barge:	Double Hull

IMO Pollution Category:	Annex I
IBC 16.2.6:	Not applicable
IBC 16.2.9:	Not applicable
Pre-Wash Required:	Not applicable
Compatibility Group:	USCG Compatibility Group 33

Cargo Handling Requirements

N2 Purge Cargo Tanks Prior Loading:	None
N2 Blanket Required:	None
Adjacent Space Purge:	None
Loading Temperature Range:	Ambient
Transit Temperature Range:	Ambient
Discharge Temperature Range:	Ambient
Maximum Heating Coil Temperature:	Not Applicable
Adjacent Maximum Cargo Temperature:	65 °C / 150 °F

Regional Requirements

None

Tank Acceptance Requirements

All nominated shipboard cargo handling systems are to be presented clean (residual free), dry, odor free, rust free, with good gaskets, fit to load this cargo.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N2, and blanked off.

Stainless Steel or Coated Tank:	Either, carrier to verify suitability of coating for product
Banned Prior Cargo:	No
Wall Wash Required:	No

Safety Information and Incident Reporting

Safety Information:

HSSE information can be found in the SDS or e-SDS.

Incident Reporting:

All incidents should be reported in accordance with regulations and charter party requirements.

International Registered Vessels: If an incident occurs call Shell International Trading and Shipping in London on +442079347777.

Jones Act Vessels: call the Shell 24 hr. incident number at +17132412532. The USA National Response Center telephone number is +18004248802.

Disclaimer

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.