



Shell Chemicals

Cargo Handling Sheet

Neodol 911

Document Date: 01 April 2018
Revision 9

Cargo Handling Sheets are for the use of vessels chartered by Shell Chemicals

Product Details

| | |
|------------------|---|
| Product Name: | Neodol 911 |
| Shipping Name: | Alcohols (C8–C11), primary, linear and essentially linear |
| Chemical Family: | Alcohols |
| Product Code: | X3085 |

SDS: <http://www.shell.com/business-customers/chemicals/safe-product-handling-and-transportation/safety-data-sheets.html>

Physical Properties

| | |
|--------------------|---------------------------------------|
| Density: | 830 kg/m ³ (20 °C / 68 °F) |
| Dynamic Viscosity: | 14.11 mPas (20 °C / 68 °F) |
| Vapor Pressure: | < 5 Pa (25 °C / 77 °F) |
| Boiling Point: | 213 - 245 °C / 415 - 473 °F |
| Pour Point: | -12 °C / 54 °F |
| Flash Point: | 109 °C / 228 °F |
| Appearance: | Colourless Liquid at 20 °C |

Note 1: Physical Properties are for reference only and valid as of date of this revision; see loading terminal for specific properties.

Transhipment Prior to arranging transhipment, Charterers must agree to Owner's proposed plan

Marpol Details

| | |
|-------------------------|-------------|
| Marpol Annex: | II |
| IMO Ship Type: | 2 |
| Inland Barge | Double Hull |
| IMO Pollution Category: | Y |
| IBC 16.2.6: | Yes |
| IBC 16.2.9: | Yes |

Pre-Wash Required: No pre-wash required when discharged in accordance with CHS
Compatibility Group: USCG compatibility group 20, not compatible with group 20 Isocyanates.

Cargo Handling Requirements

N2 Purge Cargo Tanks Prior Loading: Yes, PQ requirement; Max 1000 ppm O₂, 99.99 % N₂ Purity, see Notes below
N2 Blanket Required: Yes, PQ requirement; Max 1000 ppm O₂, 99.99 % N₂ Purity, see Notes below
Adjacent Space Purge: No
Loading Temperature Range: Ambient
Transit Temperature Range: Ambient
Discharge Temperature Range: Ambient (see Regional Requirements)
Maximum Heating Coil Temperature: Blanked off
Adjacent Maximum Cargo Temperature: < 40 °C / 104 °F

Note 1: If Nitrogen blanket is in place and Carrier chooses to tranship, carrier must reapply nitrogen blanket on the cargo, both on the discharging and receiving vessel, at their time, risk, and expense.

Note 2: PQ = Product Quality

Note 3: N₂ Blanket Guidance:

- a. O₂ level in tanks: 1000 ppm O₂, 99.99% N₂ purity
- b. After loading the tank will be purged below 1000 ppm, or for a period of 3.5 hours whichever comes first.
- c. Vessel to maintain a constant nitrogen overpressure of 20 millibars or more during the voyage
- d. Surveyor to record in survey report the type of cargo monitoring system and nitrogen replenishment system used onboard the vessel
- e. Vessel to keep a daily N₂ log of each tank:
 1. Tank pressure
 2. O₂ level
 3. Tank Temperature

Log is to be presented to receiver at time of discharge and a copy sent to Charterers.

Regional Requirements

Note 1: Short voyages in Europe: may only require blanketing, however if the short voyage is part of an international voyage, the short voyage must also have the tanks purged.

Note 2: Discharge temperature is ambient; however, heating to 16 – 21 °C is acceptable to improve pumpability in cold climates, as long as these temperatures are maintained during the voyage.

Note 3: Short Voyages in Japan (3 days or less): Pre-load purging or padding is not required.

Tank Acceptance Requirements

All nominated shipboard cargo handling systems are to be presented clean (residual free), dry, odor free, rust free, with good gaskets, fit to load this cargo.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N₂, and blanked off.

Stainless Steel or Coated Tanks: Stainless Steel
Banned Prior Cargo: Styrene or any other product which can polymerize;
Phosphoric acid, Sulphuric acid, and Caustic

Wall Wash Required: Yes

Stainless Steel Tanks: verification of shipboard WWT may be accepted if below specs are met. (Send WWT Verification to the responsible Shell Chemicals charterer and present to cargo surveyor and loading master at loading terminal.)

| Wall Wash Test: | Specification | Standard |
|-----------------|----------------|--------------|
| Hydrocarbons | Pass | ASTM D1722 |
| Chlorides | ≤ 3.0 ppm | IMPCA 002-98 |
| Colour Test | ≤ 10 Pt/Co Max | ASTM D1209 |

Link to: [WWT Verification Form](#)

Safety Information and Incident Reporting

Safety Information:

For more detailed information, refer to the SDS or e-SDS for reportable spill/release quantities whether in the water, air or ground.

Incident Reporting:

International Registered Vessels: If an incident occurs call Shell International Trading and Shipping in London on +442079347777.

Jones Act Vessels: call the Shell 24 hr. incident number at +17132412532. The USA National Response Center telephone number is +18004248802.

For additional marine cargo handling advice or information, contact Captain Stephen Boudreaux at +17132413945 or Capt. Ben van Bommel at +31104415992.



Shell Chemical LP

PO Box 4407

Houston

Texas 77210

USA

Tel +1 866 897 4355

Internet <http://www.shell.com/chemicals>

Disclaimer

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Shell Chemicals

The expression "Shell Chemicals" refers to the companies of the Shell Group of companies that are engaged in the chemical businesses. Each of the companies that make up the Shell Group of companies is an independent entity and has its own separate identity.