



Shell Chemicals

Cargo Handling Sheet

IPA

Document Date: 21 August 2020
Revision 9

*Cargo Handling Sheets are for the use of vessels
loading on behalf of Shell Chemicals*

Product Details

Product Name: IPA
IMO Product Name: Isopropyl Alcohol
Chemical Family: Alcohols
Product Code: S1111, ZA07A

SDS: <http://www.shell.com/business-customers/chemicals/safe-product-handling-and-transportation/safety-data-sheets.html>

Physical Properties

Density: 785 - 786 kg/m³ (20 °C / 68 °F)
Specific Gravity: 0.78 – 0.79 @ °C
Dynamic Viscosity: 2.43 mPa.s
Vapor Pressure: 4.1 kPa / 0.59 psi (20 °C / 68 °F)
Boiling Point: 82 - 83 °C / 180 - 181 °F
Melting Point: -88 °C / -126 °F
Flash Point: 12 °C / 54 °F
Appearance: Clear liquid with a characteristic odour

Note 1: Physical Properties are for reference only and valid as of date of this revision; see loading terminal for specific properties.

Note 2: Hazard Identification: Highly Flammable; take precautionary measures against static discharge. See SDS for full list of hazards and precautions.

Transhipment

Prior to arranging transhipment Charterer must agree to Owner's proposed plan. When arranged by the Owner, Owner must ensure that all transhipment vessels comply with the requirements of this cargo handling sheet.

Marpol Details

Marpol Annex: II
IMO Ship Type: 3; Must be Double Hulled
Inland Barges: Double Hull
IMO Pollution Category: Z

IBC 16.2.6:	No
IBC 16.2.9:	No
Pre-Wash Required:	No
Compatibility Group:	USCG compatibility group 20, not compatible with group 12 Isocyanates.

Cargo Handling Requirements

N2 Purge Cargo Tanks Prior Loading:	No
N2 Blanket Required:	No, not a PQ Requirement, see notes below
Loading Temperature Range:	Ambient
Transit Temperature Range:	Ambient
Discharge Temperature Range:	Ambient
Maximum Heating Coil Temperature:	Blanked off
Adjacent Maximum Cargo Temperature:	40 °C / 104 °F

Note 1: If vessel must inert tanks in accordance with regulation and/or Shell Chemical Inert Gas Clause, then only N2 will be accepted as an inerting medium.

Note 2: If Nitrogen blanket is in place and Carrier chooses to tranship, carrier must reapply nitrogen blanket on the cargo, both on the discharging and receiving vessel, at their time, risk, and expense.

Note 3: PQ = Product Quality

Regional Requirements

Note 1: IPA Loaded in Singapore: Banned prior and adjacent cargo list applicable

- Prior Cargo: applies to last cargo in stainless steel tanks
- Adjacent Cargoes: applies to current or future adjacent cargo. Carrier should be reminded that adjacent cargo restrictions apply throughout the voyage until the product is discharged.
- Prior and adjacent cargoes must be approved by Shell Chemicals Marine Charterer.

[APPENDICES BANNED PRIOR CARGOES AND ADJACENT CARGOES LIST \(Link\)](#)

Tank Acceptance Requirements

All nominated shipboard cargo handling systems are to be presented clean (residual free), dry, odor free, rust free, with good gaskets, fit to load this cargo.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N₂, and blanked off.

Stainless Steel or Coated Tank: Either, carrier to verify suitability of coating for product; Stainless Steel only when loaded in Singapore.
Banned Prior Cargo: No; However, see Regional Requirements if loaded in Singapore
Wall Wash Required: Yes, all conducted with Methanol except PH test, which uses DI water

Coated Tanks: WWT conducted by cargo surveyor.

Stainless Steel Tanks: verification of shipboard WWT may be accepted if below specs are met. (Send WWT Verification to the responsible Shell Chemicals charterer and present to cargo surveyor and loading master at loading terminal.)

Wall Wash Test:	Specification	Standard
Appearance	Clear and free from suspended matter	ASTM D4176
Chlorides	≤ 1.0 ppm	IMPCA 002-98
Hydrocarbons	= Pass	ASTM D1722

Additional WWT for Coated Tanks if Prior Cargo is:

Prior Cargo	Wall Wash Test:	Specification	Standard
Acrylate	PPT	> 30 minutes	ASTM D1363
Oils, Waxes, Veg Oils, Fame	NVM	100 ppm	ASTM D1353
Acids, Alkilis	PH Test	6 – 8	ASTM E70

Link to: [WWT Verification Form](#)

Safety Information and Incident Reporting

Safety Information:

HSSE information can be found in the SDS or e-SDS.

Incident Reporting:

All incidents should be reported in accordance with regulations and charter party requirements.

International Registered Vessels: If an incident occurs call Shell International Trading and Shipping in London on +442079347777.

Jones Act Vessels: call the Shell 24 hr. incident number at +17132412532. The USA National Response Center telephone number is +18004248802.

For additional marine cargo handling advice or information, contact Captain Stephen Boudreaux at +18323376982 or Capt. Ben van Bommel at +31104415992.



Shell Chemical LP
PO Box 4407
Houston
Texas 77210
USA
Tel +1 866 897 4355
Internet <http://www.shell.com/chemicals>

Disclaimer

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Shell Chemicals

The expression "Shell Chemicals" refers to the companies of the Shell Group of companies that are engaged in the chemical businesses. Each of the companies that make up the Shell Group of companies is an independent entity and has its own separate identity.