

Cargo Handling Sheet

Non-Shell Product

Benzene Concentrate (Valero)

Document Date: 30 July 2021

Revision 2

Cargo Handling Sheets are for the use of vessels chartered on behalf of Shell

Information is obtained from supplier's SDS and other reference publications.

Product Details

Product Name:	Benzene Concentrate (Valero)
IMO Product Name:	Petroleum Products, (Distillates (petroleum), C6-rich)
Chemical Family:	Aromatic Hydrocarbon
Product Code:	Valero Product ID no. 649-388-00-9
SDS:	Obtain from Valero Terminal

Physical Properties

Relative Density:	0.62 - 0.88 (15 °C / 59 °F)
Viscosity:	< 1 mm ² /s (40 °C / 104 °F)
Vapor Pressure:	4 – 240 kPa (37.8 °C / 100.0 °F)
Boiling Point:	60 - 90 °C / 140 - 194 °F
Melting Point:	Not Applicable
Flash Point:	< -5 °C / 39 °F
Appearance:	Colourless to yellow liquid with aromatic odour

Note 1: Physical Properties are for reference only and valid as of date of this revision; see loading terminal for specific properties.

Note 2: Hazard Identification: Extremely flammable, static accumulator, toxic, carcinogen, may solidify; See SDS for full list of hazards and precautions.

Transhipments

Prior to arranging transhipment Charterer must agree to Owner's proposed plan. When arranged by the Owner, Owner must ensure that all transhipment vessels comply with the requirements of this cargo handling sheet.

Marpol Details

Marpol Annex:	I
IMO Ship Type:	Double hull vessels certified for carriage of oil
Inland Barges:	Double Hull

IMO Pollution Category:	Not Applicable
IBC 16.2.6:	Not Applicable
IBC 16.2.9:	Not Applicable
Pre-Wash Required:	Not Applicable
Compatibility Group:	USCG compatibility group 32

Cargo Handling Requirements

N2 Purge Cargo Tanks Prior to Loading:	No
N2 Blanket Required:	Not a Product Quality requirement; see notes below
Adjacent Space Purge:	No
Loading Temperature Range:	Ambient
Transit Temperature Range:	Ambient - 40 °C / 104 °F
Discharge Temperature Range:	Ambient - 40 °C / 104 °F; See notes below
Maximum Heating Coil Temperature:	Blanked off
Adjacent Maximum Cargo Temperature:	40 °C / 104 °F

Note 1: If vessel is required to inert tanks then only N2 will be accepted as an inerting medium.

Note 2: If Nitrogen blanket is in place and Carrier chooses to tranship, carrier must reapply nitrogen blanket on the cargo, both on the discharging and receiving vessel, at their time, risk, and expense.

Note 3: Carrier to check with shipper to ensure correct heating requirements. Heat may be required if ambient temperature is excessively low. If heating condensate is returned to machinery spaces, then condensate returns should be tested using a benzene test kit.

Regional Requirements

None

Tank Acceptance Requirements

All nominated shipboard cargo handling systems are to be presented clean (residual free), dry, odor free, rust free, with good gaskets, fit to load this cargo.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N2 and blanked off.

Stainless Steel or Coated Tank: Either; carrier to verify suitability of coating for product

Banned Prior Cargo: No
Wall Wash Required: No

Safety Information and Incident Reporting

Safety Information:

For more detailed information, refer to the SDS or e-SDS for reportable spill/release quantities whether in the water, air or ground.

Incident Reporting for vessels on Shell charter.

International Registered Vessels: call Shell International Trading and Shipping in London on +442079347777.

Jones Act Vessels: call the Shell 24 hr. incident number at +17132412532. The USA National response centre telephone number is +18004248802.

Disclaimer

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.