



Shell

Cargo Handling Sheet

Benzene

Document Date: 30 July 2021
Revision 10

Cargo Handling Sheets are for the use of vessels chartered on behalf of Shell

Product Details

Product Name:	Benzene
IMO Product Name:	Benzene and mixtures having 10% benzene or more
Chemical Family:	Aromatic Hydrocarbon
Product Code:	Q9112, Q9121, Q9169, Q9262, Q9261
SDS:	http://www.shell.com/business-customers/chemicals/safe-product-handling-and-transportation/safety-data-sheets.html

Physical Properties

Density:	883 kg/m ³ (15 °C / 59 °F)
Dynamic Viscosity:	0.60 mPas (20 °C / 68 °F)
Vapor Pressure:	10 kPa (20 °C / 68 °F)
Boiling Point:	80.1 °C / 176.2 °F
Melting Point:	5.5 °C / 41.9 °F
Flash Point:	-11 °C / 12 °F
Auto-ignition temperature:	498 °C / 928 °F
Appearance:	Colourless liquid with aromatic odour

Note 1: Physical Properties are for reference only and valid as of date of this revision; see loading terminal for specific properties.

Note 2: Hazard Identification: Extremely flammable, static accumulator, toxic, carcinogen, may solidify; See SDS for full list of hazards and precautions.

Transhipment

Prior to arranging transhipment Charterer must agree to Owner's proposed plan. When arranged by the Owner, Owner must ensure that all transhipment vessels comply with the requirements of this cargo handling sheet.

Marpol Details

Marpol Annex:	II
IMO Ship Type:	3; must be double hull
Inland Barge:	Double Hull
IMO Pollution Category:	Y

IBC 16.2.6:	No
IBC 16.2.9:	Yes
Pre-wash Required:	No pre-wash required when discharged in accordance with CHS
Compatibility Group:	USCG compatibility group 32

Cargo Handling Requirements

N2 Purge Cargo Tanks Prior Loading:	No
N2 Blanket Required:	Not a Product Quality requirement; see notes below
Adjacent Space Purge:	No
Loading Temperature Range:	Ambient (see notes below and Regional Requirement)
Transit Temperature Range:	Ambient to 40 °C / 104 °F (see note 1 below)
Discharge Temperature Range:	Ambient to 40 °C / 104 °F (see note 1 below)
Maximum Heating Coil Temperature:	60 °C / 140 °F (see note 1 below)
Adjacent Maximum Cargo Temperature:	40 °C / 104 °F

Note 1: Minimum handling temperature for Benzene is 11 °C / 52 °F

Note 2: If loaded below 16°C / 61°F or if during voyage cargo temperature drops to < 16°C / 61°F, Shell Charterer should be notified.

Note 3: If vessel is required to inert tanks then only N2 will be accepted as an inerting medium.

Note 4: If Nitrogen blanket is in place and Carrier chooses to tranship, carrier must reapply nitrogen blanket on the cargo, both on the discharging and receiving ship, at their time, risk, and expense.

Regional Requirements

Note 1: In Europe minimum load temperature is set to 20 °C / 68 °F

Note 2: US Barge: Coatings – Stainless Steel, Mild Steel, Zinc, Epoxy; N2 not required; Vapor Return – yes; Heating – possible

Tank Acceptance Requirements

All shore and ship cargo lines and tanks are to be presented clean (residual free), dry, odor free, and rust free, with good gaskets.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N2, and blanked off.

Stainless Steel or Coated Tank: Either; carrier to verify suitability of coating for product
Banned Prior Cargo: No
Wall Wash Required: No

Safety Information and Incident Reporting

Safety Information:

HSSE information can be found in the SDS or e-SDS.

Incident Reporting:

All incidents should be reported in accordance with regulations and charter party requirements.

International Registered Vessels: If an incident occurs call Shell International Trading and Shipping in London on +442079347777.

Jones Act Vessels: call the Shell 24 hr. incident number at +17132412532. The USA National Response Center telephone number is +18004248802.

For additional marine cargo handling advice or information, contact the responsible regional Marine Technical Advisor.



Shell Chemical LP

PO Box 4407

Houston

Texas 77210

USA

Tel +1 866 897 4355

Internet <http://www.shell.com/chemicals>

Disclaimer

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Shell

The expression "Shell" refers to the companies of the Shell Group of companies that are engaged in the chemical businesses. Each of the companies that make up the Shell Group of companies is an independent entity and has its own separate identity.