



**Shell Chemicals**

# Cargo Handling Sheet

REFORMATE HC blw50 ARO blw60 deg

Document Date: 07 February 2020  
Revision 1

*Cargo Handling Sheets are for the use of vessels chartered by Shell Chemicals*

## Product Details

Product Name:	REFORMATE HC blw50 ARO blw60 deg
Shipping Name:	Benzene and mixtures having 10% benzene or more (i)
Chemical Family:	Aromatics
Product Code:	Q911B

SDS: <http://www.shell.com/business-customers/chemicals/safe-product-handling-and-transportation/safety-data-sheets.html>

## Physical Properties

Density:	Typical 790 kg/m <sup>3</sup> at 15 °C / 59 °F
Kinematic Viscosity:	0.25 – 0.75 mm <sup>2</sup> /s at 40.0 °C / 104 °F
Vapor Pressure:	20 - 60 kPa at 38.0 °C / 100 °F 30 - 108 kPa at 50.0 °C / 122 °F
Boiling Point:	Typical 60 - 110 °C / 140 - 230 °F
Melting Point:	< -30 °C / -22 °F
Flash Point:	<= 0 °C / 32 °F
Appearance:	Straw coloured, hydrocarbon/aromatic odour

**Note 1:** Physical Properties are for reference only and valid as of date of this revision; see loading terminal for specific properties.

**Note 2:** This product is a Static Accumulator

**Note 3:** This product is Toxic.

## Transshipment

Prior to arranging transshipment Charterer must agree to Owner's proposed plan. When arranged by the Owner, Owner must ensure that all transshipment vessels comply with the requirements of this cargo handling sheet.

## Marpol Details

Marpol Annex:	II
IMO Ship Type:	3, must be double hull
Inland Barges:	Double Hull
IMO Pollution Category:	Y

IBC 16.2.6:	No
IBC 16.2.9:	Yes
Pre-Wash Required:	No pre-wash required if discharged in accordance with CHS
Compatibility Group:	USCG compatibility group 32

### Cargo Handling Requirements

N2 Purge Cargo Tanks Prior Loading:	Not a PQ Requirement; See Regional Requirements below
N2 Blanket Required:	Not a PQ Requirement; see below notes and Regional Requirements
Adjacent Space Purge:	No
Loading Temperature Range:	Ambient
Transit Temperature Range:	Ambient
Discharge Temperature Range:	Ambient
Maximum Heating Coil Temperature:	Blanked off
Adjacent Maximum Cargo Temperature:	35 °C / 95 °F

**Note 1:** If vessel must inert tanks in accordance with regulation and/or Shell Chemical Inert Gas Clause, then only N2 will be accepted as an inerting medium.

**Note 2:** If Nitrogen blanket is in place and Carrier chooses to tranship, carrier must reapply nitrogen blanket on the cargo, both on the discharging and receiving vessel, at their time, risk, and expense.

**Note 3:** PQ = Product Quality.

### Regional Requirements

**Note 1:** Inter-Europe Barging: see Netherlands SDS for local requirements

**Note 2:** Shell Pernis requires N2 purging to < 8% O2 prior to loading and maintenance of N2 blanket during voyage

**Note 3:** N2 Blanket Guidance:

- a. O2 level in tanks: < 8%
- b. Vessel to maintain a constant nitrogen overpressure of 20 millibars or more during the voyage
- c. Vessel to keep a daily N2 log of each tank:
  1. Tank pressure
  2. O2 level
  3. Tank Temperature

Log is to be presented to receiver at time of discharge and a copy sent to Charterers.

## Tank Acceptance Requirements

All nominated shipboard cargo handling systems are to be presented clean (residual free), dry, odor free, rust free, with good gaskets, fit to load this cargo.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N<sub>2</sub>, and blanked off.

Stainless Steel or Coated Tank:	Either, carrier to verify suitability of coating for product
Prior Cargo Restrictions:	No
Wall Wash Required:	No

## Safety Information and Incident Reporting

### Safety Information:

For more detailed information, refer to the SDS or e-SDS for reportable spill/release quantities whether in the water, air or ground.

### Incident Reporting:

International Registered Vessels: If an incident occurs call Shell International Trading and Shipping in London on +442079347777.

Jones Act Vessels: call the Shell 24 hr. incident number at +17132412532. The USA National Response Center telephone number is +18004248802.

For additional marine cargo handling advice or information, contact Captain Stephen Boudreaux at +18323376982 or Capt. Ben van Bemmelen at +31104415992.



**Shell Chemical LP**

PO Box 4407

Houston

Texas 77210

USA

Tel +1 866 897 4355

**Internet <http://www.shell.com/chemicals>**

**Disclaimer**

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

**Shell Chemicals**

The expression "Shell Chemicals" refers to the companies of the Shell Group of companies that are engaged in the chemical businesses. Each of the companies that make up the Shell Group of companies is an independent entity and has its own separate identity.