



Shell Chemicals

Cargo Handling Sheet

Shell GTL Solvent GS 1927 HF

Document Date: 20 March 2020
Revision 3

Cargo Handling Sheets are for the use of vessels chartered by Shell Chemicals

Product Details

Product Name:	Shell GTL Solvent GS 1927 HF
Shipping Name:	Gas Oil (See Cargo Handling Requirement note below)
Chemical Family:	Alkanes, C11-C16-branched and linear
Product Code:	Q6562

SDS: <http://www.shell.com/business-customers/chemicals/safe-product-handling-and-transportation/safety-data-sheets.html>

Physical Properties

Density:	ca. 0.763 g/cm ³ (15 °C / 59 °F)
Kinematic Viscosity:	< 0.2 mm ² /s (25 °C / 77 °F)
Vapor Pressure:	< 0.001 kPa (25 °C / 77 °F)
Boiling Point:	206 - 261 °C / 403 – 502 °F
Melting Point:	Not Available
Flash Point:	> 78°C / 173 °F
Appearance:	Colourless liquid, odourless

Note 1: Physical Properties are for reference only and valid as of date of this revision; see loading terminal for specific properties.

Note 2: This product is a Static Accumulator.

Transhipment

Prior to arranging transhipment Charterer must agree to Owner's proposed plan. When arranged by the Owner, Owner must ensure that all transhipment vessels comply with the requirements of this cargo handling sheet.

Marpol Details

Marpol Annex:	Annex I
IMO Ship Type:	Double Hull vessels certified for carriage of oil
Inland Barges:	Double Hull
IMO Pollution Category:	Annex I
IBC 16.2.6:	Not Applicable
IBC 16.2.9:	Not Applicable

Pre-Wash Required: Not Applicable; wash/disposal as per Annex I

Compatibility Group: USCG compatibility group 33

Cargo Handling Requirements

N2 Purge Cargo Tanks Prior Loading:	No
N2 Blanket Required:	No
Adjacent Space Purge:	No
Loading Temperature Range:	Ambient – 30 °C / 86 °F
Transit Temperature Range:	Ambient – Loading Temp
Discharge Temperature Range:	Ambient – Loading Temp
Maximum Heating Coil Temperature:	Blanked off; does not require heat
Adjacent Maximum Cargo Temperature:	55 °C / 131 °F

Note 1: Shipping name is "Gas Oil". However, when product is shipped by Shell Chemicals, it should be treated as a water-white chemical susceptible to aromatics.

Regional Requirements

None

Tank Acceptance Requirements

All nominated shipboard cargo handling systems are to be presented clean (residual free), dry, odor free, rust free, with good gaskets, fit to load this cargo.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N2, and blanked off.

Stainless Steel or Coated Tank:	Either, carrier to verify suitability of coating for product
Banned Prior Cargo:	No
Wall Wash Required:	Yes, After Aromatics only; WWT conducted with methanol except PH test, which uses DI water

Coated Tanks: WWT conducted by cargo surveyor.

Stainless Steel Tanks: verification of shipboard WWT may be accepted if below specs are met. (Send WWT Verification to the responsible Shell Chemicals charterer and present to cargo surveyor and loading master at loading terminal.)

Wall Wash Test:	Specification	Standard
Appearance	Clear and free from suspended matter	ASTM D4176
Chlorides	≤ 5.0 ppm	IMPCA 002-98
Hydrocarbons	= Pass	ASTM D1722
Color Test	Max 5 Pt/Co Max	ASTM D1209

Additional WWT for Coated Tanks if Prior Cargo is:

Prior Cargo	Wall Wash Test:	Specification	Standard
Acrylate	PPT	> 30 minutes	ASTM D1363
Oils, Waxes, Veg Oils, Fame	NVM	100 ppm	ASTM D1353
Acids, Alkalís	PH Test	6 – 8	ASTM E70

Link to: [WWT Verification Form](#)

Safety Information and Incident Reporting

Safety Information:

For more detailed information, refer to the SDS or e-SDS for reportable spill/release quantities whether in the water, air or ground.

Incident Reporting:

International Registered Vessels: If an incident occurs call Shell International Trading and Shipping in London on +442079347777.

Jones Act Vessels: call the Shell 24 hr. incident number at +17132412532. The USA National Response Center telephone number is +18004248802.

For additional marine cargo handling advice or information, contact Captain Stephen Boudreaux at +18323376982 or Capt. Ben van Bommel at +31 104415992.



Shell Chemical LP
PO Box 4407
Houston
Texas 77210
USA
Tel +1 866 897 4355
Internet <http://www.shell.com/chemicals>

Disclaimer

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Shell Chemicals

The expression "Shell Chemicals" refers to the companies of the Shell Group of companies that are engaged in the chemical businesses. Each of the companies that make up the Shell Group of companies is an independent entity and has its own separate identity.