

Shell MDS (Malaysia) Sendirian Berhad

Date prepared: 20th APRIL 2021

Supersedes: 16th Feb 2015

CARGO HANDLING REQUIREMENTS

Shell GTL SARALINE 185V

1. PRODUCT DETAILS

Product name : SHELL GT SARALINE 185V

Alternate Product Name : Distilates, C8-26 (Fisher-Tropsch) branched and linear

Product Code : 002D6227

CAS No : 848301-67-7

Emergency telephone number: +60-86 292 222

2. PHYSICAL AND CHEMICAL PROPERTIES

Colour: Colourless
Odour: Paraffinic

Odour Threshold: Data not available

Vapour pressure<=0.1 kPa (25.0 °C / 77.0 °F)</th>Boiling point/Boiling range:200 -320 °C (392 -608 °F)

Evaporation rate: Data not available

Solubility in Water: Negligible

Density: 780 kg/m³ (15°C / 59.0 °F)

Flash point: >=85 °C / 185 °F

Flammable limits Lower/Upper: lower: 0.5%; upper:5.0% (V/V)

Auto-ignition temperature: 210°C / 410.0 °F

Kinematic viscosity: 2.6 mm²/s (40°C / 104.0 °F)

Relative Vapour density: Data not available

Partition co-efficient, n-

octanol/water: >6.5

Explosive properties: In use, may form flammable/explosive vapour-air

mixtures.

3. TRANSSHIPMENTS

Notes: Transshipments (Ship/Ship & Ship/Barge) usually permitted but operations is dependent on risk assessement (location of operation, vessels used, nature of products etc.). Consult regional MTA for advise and clearance <u>prior</u> to fixing transshipment operation.

4. MARPOL DETAILS

Shipping Name: GAS OIL

Marpol Annex:

Ship Type: Oil Tanker

IMO Pollution Category: N/A

Pre Wash: Not applicable, wash/disposal as per Annex I

High Viscosity: NO Solidifying: NO

Minimum Unloading Temperature : Ambient

5. CARGO HANDLING CRITERIA

All shore, ship, cargo line and tanks are to be presented (residual free) gas free, dry, ordour free, and rust free, with good gaskets and pressure tested steam coils.

Pre-purging of Vessel's Tanks : NO N2 blanket required: NO

Loading Temperature range:

Transit Temperature:

Discharge Temperature:

Max heating coil Temperature:

N/A

Adjacent Max.cargo Temperature: Ambient

Cargo handling Notes:

6. TANK ACCEPTANCE CRITERIA

Stainless Steel or Coated Tanks: Coated Tanks

Wall Wash Required: NO

Wash Notes:

Tank Acceptance Notes: Maintenance of steam coils is to be verified with the ship's

log. If products is to be heated, steam coils are to be

confirmed leak free. If products is not heated, steam coils are to be drained, dry, clean, blanked off and steam source is to

be isolated from the tanks.

7. SAFETY INFORMATION AND INCIDENT REPORTING

Safety Information :-

For more information, refer to SDS and to EDS for reportable spill/release quantities whether in water, air or ground.

CASUALTY NOTIFICATION PROCEDURE

IN THE EVENT OF AN INCIDENT AS DESCRIBED BELOW, SHELL CASUALTY MUST BE NOTIFIED WITHIN ONE HOUR OF THE INCIDENT OCCURING:

- · AN INCIDENT WHICH MIGHT OR HAS PUT AT RISK THE LIVES OF PERSONS AND/OR THE SAFETY OF THE VESSEL AND/OR THE ENVIRONMENT AND WHOSE CONSEQUENCES HAVE OR MIGHT INVOLVE OTHER SHELL COMPANIES, THIRD PARTIES, GOVERNMENTS OR THE MEDIA.
- · A LOSS OF PRIMARY CONTAINMENT OF OIL, GAS (LNG/LPG), CHEMICALS, OR BULK CARGO, OWNED BY A SHELL COMPANY OR AT AS SHELL FACILITY, OR FROM A SHIP MANAGED OR CHARTERED BY A SHELL COMPANY.
- · A SIGNIFICANT DELAY TO ANY SHIP WHOSE CHARTER, CARGO OR BERTH INVOLVES A SHELL COMPANY
- · AN INCIDENT OF ALLEGED NON COMPLIANCE WHERE REGULATORS HAVE OR MAY BECOME INVOLVED.
- · A SECURITY INCIDENT INCLUDING A SUSPICIOUS PIRACY APPROACH OR PIRACY ATTACK
- · AN ACTUAL, POTENTIAL OR SUSPECTED IMPACT TO CREW OR VESSEL FROM ANY SERIOUS INFECTIOUS DISESE (INCLUDING BUT NOT LIMITED TO COVID-19)

NOTIFICATION SHOULD BE MADE IN THE FOLLOWING ORDER OF PRIORITY.

- BY TELEPHONE: (+44)-207-934-7777, THE DEDICATED TELEPHONE NUMBER FOR CASUALTIES, (24 HOURS).
- BY EMAIL: casualtyalert@shell.com
- BY TELEX: SHELLCASUALTY LONDON 8814807

THE FOLLOWING INFORMATION MUST BE INCLUDED IN THE MESSAGE:

- · NAME OF THE VESSEL
- TIME AND DESCRIPTION OF INCIDENT (INCLUDE ESTIMATED EXTENT OF DAMAGE)
- · GEOGRAPHICAL LOCATION AND DISTANCE FROM NEAREST GROUNDING LINE
- · IS THE VESSEL ABLE TO CONTINUE THE VOYAGE AND WHAT IS THE EXPECTED DURATION OF DELAY (IF ANY)
- · 24 HR TELEPHONE NUMBER OF COMPANY DPA
- · TYPE OF SHELL CHARTER (VOYAGE, TIME, SPACE OR OTHER- IF KNOWN)
- · NAME OF SHELL CONTACT IF KNOWN

IN THE EVENT OF AN OIL/CHEMICAL/ GAS SPILL, THE MESSAGE MUST ALSO INCLUDE:

- · LOCAL TIME, DATE AND LOCATION OF SPILL, INDICATING NAME OF OWNER OF THE INSTALLATION (IF IN PORT) AND WHETHER AT A JETTY/CBM/SBM OR AT SEA.
- \cdot Type of Oil/Gas /Chemical e.g. crude/black/white/lubes/bitumen etc.
- · CAUSE IF KNOWN E.G. OVERFLOW HOSE BURST DEFECTIVE SHORE LINE HULL DEFECT ETC.
- · ESTIMATED QUANTITY SPILLED
- · ESTIMATE OF RATE OF SPILL IF CONTINUING
- $\,\cdot\,$ Whether Clean-up has been attempted, either by Ship or third party
- · ANY OTHER RELEVANT COMMENTS
- · TIME OF ORIGIN OF EACH REPORT.

IF THE ACCIDENT OCCURS WITHIN PORT THE AGENT MUST ALSO BE COPIED ON ALL MESSAGES SENT TO SHELL

THE FOREGOING REQUIREMENTS ARE IN ADDITION TO ANY CASUALTY REPORTING PROCEDURE SYSTEM VESSEL'S OWNERS/MANAGERS MAY HAVE, PARTICULARLY WITH RESPECT TO US QI REPORTING REQUIREMENTS.