

## **Shell Chemicals**

# Cargo Handling Sheet

Sarasol 150/200

Document Date: 21 July 2017

Revision 4

Cargo Handling Sheets are for the use of vessels chartered by Shell Chemicals

Cargo Handling Sheet: Sarasol 150/200 Document Date: 21 July 2017

Revision 4

#### **Product Details**

Product Name: Sarasol 150/200 (Brightsol)

Shipping Name: Kerosene

Chemical Family: Alkanes

Product Code: Q6532

SDS: <a href="http://www.shell.com/business-customers/chemicals/safe-product-handling-and-transportation/safety-data-sheets.html">http://www.shell.com/business-customers/chemicals/safe-product-handling-and-transportation/safety-data-sheets.html</a>

#### **Physical Properties**

Density: Not Available

Kinematic Viscosity: Not Available

Vapor Pressure: Not Available

Boiling Point: Typical 157 - 213 °C

Melting Point: Not Available

Flash Point: Typical 43 °C

Appearance: Light coloured

Note 1: Physical Properties are for reference only and valid as of date of this revision; see loading terminal for specific properties.

Note 2: This product is a Static Accumulator

**Transhipment** Prior to arranging transhipment, Charterers must agree to Owner's

proposed plan

#### Marpol Details

Marpol Annex:

IMO Ship Type: Double hull vessels certified for carriage of oil

Inland Barge: Double Hull

IMO Pollution Category: Annex I

IBC 16.2.6: Not Applicable

IBC 16.2.9: Not Applicable

Pre-Wash Required: Not Applicable; wash/disposal as per Annex I

Cargo Handling Sheet: Sarasol 150/200 Document Date: 21 July 2017

Revision 4

Compatibility Group: USCG compatibility group 33

#### Cargo Handling Criteria

N2 Purge Cargo Tanks Prior Loading: No, not a PQ requirement

N2 Blanket Required:

No, not a PQ requirement; see Notes below and

Regional Requirements

Percent Oxygen in Nitrogen Blanket: <8%, if required

Adjacent Space Purge: No

Loading Temperature Range: Ambient

Transit Temperature Range: Ambient

Discharge Temperature Range: Ambient

Maximum Heating Coil Temperature: Blanked off

Adjacent Maximum Cargo Temperature: 40 °C

Note 1: If vessel must inert tanks in accordance with regulation and/or Shell Chemical Inert Gas Clause, then only N2 will be accepted as an inerting medium.

Note 2: If Nitrogen blanket is in place and Carrier chooses to tranship, carrier must reapply nitrogen blanket on the cargo, both on the discharging and receiving vessel, at their time, risk, and expense.

Note 3: PQ = Product Quality

#### Regional Requirements

Note 1: Short Voyages in Japan (3 days or less): Pre-load purging or padding is not required.

## Tank Acceptance Requirements

All nominated shipboard cargo handling systems are to be presented clean (residual free), dry, odor free, rust free, with good gaskets, fit to load this cargo.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N2, and blanked off.

Stainless Steel or Coated Tank: Either, carrier to verify suitability of coating for product

Prior Cargo Restrictions: No Wall Wash Required: No

Cargo Handling Sheet: Sarasol 150/200 Document Date: 21 July 2017 Revision 4

#### Safety Information and Incident Reporting

### Safety Information:

For more detailed information, refer to the SDS or e-SDS for reportable spill/release quantities whether in the water, air or ground.

#### **Incident Reporting:**

International Registered Vessels: If an incident occurs call Shell International Trading and Shipping in London on +442079347777.

Jones Act Vessels: call the Shell 24 hr. incident number at +17132412532. The USA National Response Center telephone number is +18004248802.

For additional marine cargo handling advice or information, contact Captain Stephen Boudreaux at +17132413945 or Capt. Ben van Bemmel at +31104415992.



Shell Chemical LP
PO Box 4407
Houston
Texas 77210
USA
Tel +1 866 897 4355
Internet http://www.shell.com/chemicals

#### Disclaimer

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

#### Shell Chemicals

The expression "Shell Chemicals" refers to the companies of the Shell Group of companies that are engaged in the chemical businesses. Each of the companies that make up the Shell Group of companies is an independent entity and has its own separate identity.