



Hexane Extraction grade

TECHNICAL DATASHEET

Special Boiling Point Solvent
SICC Product Code: Q1252
CAS Registry Number: 64742-49-0
EC Number: 925-292-5

Description

Hexane Extraction Grade is manufactured to the high standards required by the food and extraction industry. The solvent contains about 46% n-hexane. It is very low in aromatics, olefins and other impurities.

Typical Physical Properties

Property	Unit	Value	Method
Density @ 15°C	kg/l	0.678	ASTM D4052
Coefficient of Cubic Expansion @ 20°C	10 ⁻⁴	13	calculated
Refractive Index @ 20°C	-	1.380	ASTM D1218
Colour	Saybolt	+30	ASTM D156
Bromine index	mg Br/100g	< 5	ASTM D2710
Copper Corrosion (1hr @ 100°C)	-	1	ASTM D130
Doctor Test	-	Negative	ASTM D4952
Non-Volatile Matter	mg/100 ml	< 0.5	ASTM D1353
Distillation, Initial Boiling Point	°C	66	ASTM D1078
Distillation, Dry Point	°C	69	ASTM D1078
Relative Evaporation rate (nBuAc=1)	-	8.0	ASTM D3539
Antoine Constant A [#]	kPa, °C	7.38070	-
Antoine Constant B [#]	kPa, °C	2110.27	-
Antoine Constant C [#]	kPa, °C	326.200	-

Notes:

[#]: In the Antoine temperature range, the vapor pressure P (kPa) at temperature T (°C) can be calculated by means of the Antoine equation:
 $\log P = A - B/(T+C)$.



Typical Physical Properties

Property	Unit	Value	Method
Antoine Constants: Temperature range	°C	+20 to +70	-
Vapor Pressure @ 0°C	kPa	8.2	Calculated
Vapor Pressure @ 20°C	kPa	19	Calculated
Saturated Vapor Concentration @ 20°C	g/m ³	681	Calculated
Paraffins	%m/m	80	GC
Napthenes	%m/m	20	GC
Aromatics	mg/kg	< 5	SMS 2728
Benzene	mg/kg	< 3	GC
n-Hexane	%m/m	46	GC
Water	%m/m	< 0.006	ASTM E1064
Sulfur	mg/kg	< 0.5	ISO 20846
Flashpoint, (Abel)	°C	-30	IP170
Lower Explosion Limit in Air	%v/v	1.1	
Upper Explosion Limit in Air	%v/v	7.4	
Auto Ignition Temperature	°C	375	ASTM E659
Electric Conductivity @ 20°C	pS/m	< 1	ASTM D4308
Dielectric Constant	-	1.9	-
Aniline Point	°C	65	ASTM D611
Pour Point	°C	< -50	ASTM D97
Viscosity @ 25°C	mm ² /s	0.46	ASTM D445
Surface Tension @ 20°C	mN/m	19	Du Nouy ring
Thermal Conductivity @ 20°C	W/m/°C	0.12	-
Hildebrand Solubility Parameter	(cal/cm ³) ^{1/2}	7.3	
Hydrogen Bonding Index	-	0	-
Fraction Polarity	-	0	-
Heat of Vaporization at T _{boil}	kJ/kg	333	-
Heat of Combustion (Net) @ 25°C	kJ/kg	46000	-
Specific Heat @ 20°C	kJ/kg/°C	2.2	-



Property	Unit	Value	Method
Molecular Weight	g/mol	86	Calculated

Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

- American Society for Testing and Materials (ASTM)
- International Organization for Standardization (ISO)
- Deutsches Institut für Normung (DIN)

Shell Method Series (SMS) methods are issued by Shell Global Solutions International B.V., Shell Technology Centre, Amsterdam, The Netherlands. Requests for copies of SMS can be made through your local Shell Chemicals company.

N.B: For routine quality control local test methods may be applied. Such methods have been validated against those mentioned in this datasheet.

Quality

Hexane Extraction grade's composition complies with the FAO/WHO specifications for polycyclic aromatics and heavy metals. Hexane Extraction grade does not contain detectable quantities of chlorinated compounds.

Hazard Information

For detailed Hazard Information please refer to the Safety Data Sheet.

Access Safety Data Sheets here: [Safety Data Sheets](#)

Storage and Handling

Provided proper storage and handling precautions are taken we would expect Hexane Extraction grade to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Safety Data Sheet

Shell Warranties

All products purchased or supplied by Shell chemicals companies are subject to the terms and conditions set out in the contract, order confirmation and/or bill of lading. All other information supplied by Shell chemicals companies, including that herein, is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine a product's suitability for a particular purpose. Except as may be set forth in the applicable contract, order confirmation and/or bill of lading, Shell chemicals companies make no warranty, express or implied, including regarding any information supplied or the data upon which it is based or the results to be



Shell Chemicals

obtained from the use of such products or information, or concerning product, whether of satisfactory quality, merchantability, fitness for any particular purpose or otherwise, or with respect to intellectual property infringement as a result of use of information or products, and none shall be implied.

The expression 'Shell Chemicals' refers to the companies of Shell Plc./Shell Group that are engaged in chemical businesses. Each of the companies that make up Shell Plc./Shell Group of companies is an independent entity and has its own separate identity.

Learn more at www.shell.com/chemicals