



Shell Chemicals

# ShellSol® A150

## TECHNICAL DATASHEET

Aromatic Solvents  
SICC Product Code: Q7493  
CAS Registry Number: 64742-94-5  
EC Number: 919-284-0

### Description

ShellSol® A150 is a C<sub>10</sub> aromatic hydrocarbon solvent.

### Typical Physical Properties

Property	Unit	Value	Method
Density @ 15°C	kg/l	0.888	ASTM D4052
Coefficient of Cubic Expansion @ 20°C	10 <sup>-4</sup>	9	calculated
Refractive Index @ 20°C	-	1.508	ASTM D1218
Colour	Saybolt	+30	ASTM D156
Copper Corrosion (1hr @ 100°C)	-	1	ASTM D130
Doctor Test	-	Negative	ASTM D4952
Non-Volatile Matter	mg/100 ml	1	ASTM D1353
Distillation, Initial Boiling Point	°C	188	ASTM D86
Distillation, Dry Point	°C	198	ASTM D86
Relative Evaporation rate (nBuAc=1)	-	0.06	ASTM D3539
Antoine Constant A <sup>#</sup>	kPa, °C	7.45653	-
Antoine Constant B <sup>#</sup>	kPa, °C	2459.76	-
Antoine Constant C <sup>#</sup>	kPa, °C	269.313	-
Antoine Constants: Temperature range	°C	+20 to +140	-

Notes:

#: In the Antoine temperature range, the vapor pressure P (kPa) at temperature T (°C) can be calculated by means of the Antoine equation:

$$\log P = A - B/(T+C).$$



## Typical Physical Properties

Property	Unit	Value	Method
Vapor Pressure @ 0°C	kPa	0.02	Calculated
Vapor Pressure @ 20°C	kPa	0.09	Calculated
Saturated Vapor Concentration @ 20°C	g/m <sup>3</sup>	5	Calculated
Aromatics	% m/m	> 99	GC
Benzene	mg/kg	< 3	GC
Sulfur	mg/kg	< 0.5	ISO 20846
Flashpoint	°C	63	ASTM D93
Lower Explosion Limit in Air	%v/v	0.6	-
Upper Explosion Limit in Air	%v/v	7.0	-
Auto Ignition Temperature	°C	496	ASTM E659
Electric Conductivity @ 20°C	pS/m	< 10	ASTM D4308
Dielectric constant @ 20°C	-	2.4	-
Aniline Point, Mixed	°C	15	ASTM D611
Kauri-Butanol value	-	95	ASTM D1133
Pour Point	°C	< -15	ASTM D97
Viscosity @ 25°C	mm <sup>2</sup> /s	1.2	ASTM D445
Surface Tension @ 20°C	mN/m	30	Du Nouy ring
Hildebrand Solubility Parameter	(cal/cm <sup>3</sup> ) <sup>1/2</sup>	8.7	-
Hydrogen Bonding Index	-	5.3	-
Fraction Polarity	-	0.001	-
Heat of Vaporization at T <sub>boil</sub>	kJ/kg	295	-
Heat of Combustion (Net) @t 25°C	kJ/kg	42000	-
Specific Heat @ 20°C	kJ/kg/°C	1.8	-
Thermal Conductivity @ 20°C	W/m/°C	0.13	-
Molecular Weight	g/mol	130	Calculated



## Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

- American Society for Testing and Materials (ASTM)
- International Organization for Standardization (ISO)
- Deutsches Institut für Normung (DIN)

Shell Method Series (SMS) methods are issued by Shell Global Solutions International B.V., Shell Technology Centre, Amsterdam, The Netherlands. Requests for copies of SMS can be made through your local Shell Chemicals company.

N.B: For routine quality control local test methods may be applied. Such methods have been validated against those mentioned in this datasheet.

## Quality

ShellSol® A150 does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

## Hazard Information

For detailed Hazard Information please refer to the Safety Data Sheet.

Access Safety Data Sheets here: [Safety Data Sheets](#)

## Storage and Handling

Provided proper storage and handling precautions are taken we would expect ShellSol® A150 to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Safety Data Sheet

## Shell Warranties

All products purchased or supplied by Shell chemicals companies are subject to the terms and conditions set out in the contract, order confirmation and/or bill of lading. All other information supplied by Shell chemicals companies, including that herein, is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine a product's suitability for a particular purpose. Except as may be set forth in the applicable contract, order confirmation and/or bill of lading, Shell chemicals companies make no warranty, express or implied, including regarding any information supplied or the data upon which it is based or the results to be obtained from the use of such products or information, or concerning product, whether of satisfactory quality, merchantability, fitness for any particular purpose or otherwise, or



**Shell Chemicals**

with respect to intellectual property infringement as a result of use of information or products, and none shall be implied.

The expression 'Shell Chemicals' refers to the companies of Shell Plc./Shell Group that are engaged in chemical businesses. Each of the companies that make up Shell Plc./Shell Group of companies is an independent entity and has its own separate identity.

ShellSol® is a Shell trademark

Learn more at [www.shell.com/chemicals](http://www.shell.com/chemicals)