



Shell

Cargo Handling Sheet

Toluene

Document date: 12 May 2023
Revision 5

*Cargo Handling Sheets are for the use of vessels
chartered on behalf of Shell*

Product Details

Trade Name: Toluene
IMO Product Name: Toluene
Chemical Family: Aromatic Hydrocarbon
Product Code: Q9131, Q9138, Q9250, Q9300, Q9308, T1402, X211H
SDS: <http://www.shell.com/business-customers/chemicals/safe-product-handling-and-transportation/safety-data-sheets.html>

Physical Properties

Density: 871 kg/m³ (15 °C / 59 °F)
Kinematic Viscosity: 0.63 mm²/s (25 °C / 77 °F)
Vapor Pressure: 3.5 kPa (20 °C / 68 °F)
Boiling Point: 110 - 111 °C / 230 - 232 °F
Melting Point: -95 °C / -139 °F
Flash Point: 4 °C / 39 °F
Appearance: Colourless

Note 1: Physical Properties are for reference only and valid as of date of this revision; see loading terminal for specific properties.

Note 2: Hazard Identification: Highly flammable, Static accumulator. See SDS for full list of hazards and precautions.

Transhipment

Prior to arranging transhipment Charterer must agree to Owner's proposed plan. When arranged by the Owner, Owner must ensure that all transhipment vessels comply with the requirements of this cargo handling sheet.

Marpol Details

Marpol Annex: II
IMO Ship Type: 3, must be double hull
Inland Barge: Double hull
IMO Pollution Category: Y
IBC16.2.6: No

IBC 16.2.9: No
Pre-Wash Required: No
Compatibility Group: USCG compatibility group 32

Cargo Handling Requirements

N2 Purge Cargo Tanks Prior Loading Not a Product Quality requirement; see notes below
N2 Blanket Required: No a Product Quality requirement; see noted below
Adjacent Space Purge: No
Loading Temperature Range: Ambient – 40 °C / 104 °F
Transit Temperature Range: Ambient – 40 °C / 104 °F
Unloading Temperature Range: Ambient – 40 °C / 104 °F
Maximum Heating Coil Temperature: Blanked off
Maximum Adjacent Temperature: 40 °C / 104 °F

Note 1: If vessel is required to inert tanks, then only N2 will be accepted as an inerting medium.

Note 2: If Nitrogen blanket is in place and Carrier chooses to tranship, carrier must reapply nitrogen blanket on the cargo, both on the unloading and receiving vessel, at their time, risk, and expense.

Regional Requirements

Note 3: US Barge: Coatings acceptable Stainless Steel, Mild Steel, Zinc, Epoxy; N2 not required / N2 pre-load purge and after load N2 pad required. Vapor Return – may be required depending on terminal Air Quality Permit; Heating – No

Tank Acceptance Requirements

All nominated shipboard cargo handling systems are to be presented clean (residual free), dry, odor free, rust free, with good gaskets, fit to load this cargo.

Maintenance of heating coils is to be verified in the ship's log. If product is to be heated, heating coils are to be confirmed leak free. If product is not heated, heating coils are to be blown clear and dried with N2, and blanked off.

Stainless Steel or Coated Tank: Either, carrier to verify suitability of coating for product
Prior Cargo Restrictions: No
Wall Wash Required: No

Safety Information and Incident Reporting

Safety Information: Refer the SDS (Safety Data Sheet) or e-SDS.

Incident Reporting: All incidents should be reported in accordance with regulations and charter party requirements.

For additional marine cargo handling advice or information, contact the regional Chemical Marine Technical Advisor.



Shell Chemical LP

PO Box 4407

Houston

Texas 77210 USA

Disclaimer

The information contained in this publication is, to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Shell

The expression "Shell" refers to the companies of the Shell Group of companies that are engaged in the chemical businesses. Each of the companies that make up the Shell Group of companies is an independent entity and has its own separate identity.